



SCANSONIC

H I F I L O U D S P E A K E R S





scansonics-series o

The Scansonic S-Series. This family consists of 5 very different loudspeakers but all with a similar look. The beautiful high gloss finish combined with rounded edges makes the Scansonic S-series complete.

The outside is flawless, but the inside is a perfect match as well.

The S-series driver line-up of woofers and midranges with aluminium diecast baskets and 25mm soft dome tweeters with neodymium magnets ensures a remarkable performance with a fast, precise and detailed reproduction of your music.

The S-series sound response is warm, accurate and distortion free at all volume levels.



Included for S4, S5 and S6 speakers are 2 wall brackets. A flatmount and a 15° bracket. Everything about the S-series is just carefully thought out.

sound&style



System: 2-way sealed box
 Tweeter: 25 mm soft dome
 Woofer: 100 mm aluminium diecast basket
 Power: 10-100 Watt (Recommended amplifier)
 Impedance: 8 Ohm (min. 4 Ohm)
 Sensitivity: 86 dB measured at 1 watt / 1 metre
 Frequency: 60-20.000 Hz
 Crossover: 4.900 Hz
 Terminal: Binding posts (wire or 4 mm banana-plugs)
 Dimensions: 194 x 132 x 161 mm (HxWxD)
 Accessories: 2 wallbrackets (Flatmount and 15)
 Finish: High gloss paint



System: 2-way sealed box
 Tweeter: 25 mm soft dome
 Woofer: 130 mm aluminium diecast basket
 Power: 10-120 Watt (Recommended amplifier)
 Impedance: 8 Ohm (min. 4 Ohm)
 Sensitivity: 88 dB measured at 1 watt / 1 metre
 Frequency: 50-20.000 Hz
 Crossover: 4.500 Hz
 Terminal: Binding posts (wire or 4 mm banana-plugs)
 Dimensions: 223 x 151 x 210 mm (HxWxD)
 Accessories: 2 wallbrackets (Flatmount and 15)
 Finish: High gloss paint



System: 2-way sealed box
 Tweeter: 25 mm soft dome
 Woofer: 2x100 mm aluminium diecast basket
 Power: 10-150 Watt (Recommended amplifier)
 Impedance: 8 Ohm (min. 4 Ohm)
 Sensitivity: 89 dB measured at 1 watt / 1 metre
 Frequency: 50-20.000 Hz
 Crossover: 3.000 Hz
 Terminal: Binding posts (wire or 4 mm banana-plugs)
 Dimensions: 132 x 340 x 199 mm (HxWxD)
 Accessories: 2 wallbrackets (Flatmount and 15)
 Finish: High gloss paint



System: Active subwoofer
 Amplifier: 100 Watts RMS
 Woofer: 8" (200 mm) long throw woofer, diecast basket
 Frequency: Adjustable 30-160 Hz
 Crossover: Electronic
 Volume: Adjustable
 Phase: Adjustable 0-180
 Input: RCA line signal
 Input sensitivity: 90mV
 Output: RCA line signal (additional subwoofer)
 Mains Voltage: 220-240V AC
 Autostandby: Yes
 Dimensions: 303 x 270 x 270 mm (HxWxD)
 Finish: High gloss paint



System: 3-way bassreflex
 Tweeter: 25 mm soft dome
 Midrange: 100 mm aluminium diecast basket
 Woofer: 2x100 mm aluminium diecast basket
 Power: 10-200 Watt (Recommended amplifier)
 Impedance: 8 Ohm (min. 4 Ohm)
 Sensitivity: 89 dB measured at 1 watt / 1 metre
 Frequency: 45-20.000 Hz
 Crossover: 2.500 / 5.000 Hz
 Terminal: Biwiring posts (wire or 4 mm banana-plugs)
 Dimensions: 933 x 132 x 368 mm (HxWxD)
 Finish: High gloss paint





scansonic international

Bransagervej 15
DK-9490 Pandrup
Denmark

T: [+45] 98 24 76 77

F: [+45] 98 20 40 15

sales@scansonic.dk

www.scansonic.dk