

SKS-HT528 5.1-Channel Home Theatre Speaker System

BLACK



Bringing Immersive Surround Sound to Your Entertainment Zone

To get the most out of your Onkyo multichannel A/V receiver, you need to partner it with a compatible speaker package—one like the SKS-HT528. This 5.1-channel system comprises five full-range bass-reflex speakers rated at 120 W and a beefy, down-firing 150 W subwoofer. Together, they create a well-balanced, fully enveloping soundstage that brings your movies and music convincingly to life. Color-coded speaker cables and terminals make for an easy set-up, while wall-mounting capability provides extra layout options in your entertainment space. The system comes in a stylish black gloss finish that matches practically any room décor and any other component.

SKF-528 Full-Range Bass Reflex Front Speakers

- 8 cm Cone
- Max. Input Power: 120 W
- Gloss Finished
- Magnetically Shielded

SKC-528 Full-Range Bass Reflex Center Speaker

- 8 cm Cone
- Max. Input Power: 120 W
- Gloss Finished
- Magnetically Shielded

SKR-528 Full-Range Bass Reflex Surround Speakers

- 8 cm Cone
- Max. Input Power: 120 W
- Gloss Finished

Note: All speakers feature a gloss finish, an impedance of 6 Ω, color-coded speaker terminals and cable, and wall-mounting capability.

SKW-501 Bass Reflex Powered Subwoofer

- 20 cm Cone
- Down-Firing
- Max. Output Power: 150 W
- Auto Standby/On Circuitry

SPECIFICATIONS

Speaker Type		General	
Front	Full-range, bass reflex	Dimensions (W x H x D)	
Center	Full-range, bass reflex	Front	101 x 175 x 116 mm
Surround	Full-range, bass reflex	Center	273 x 101 x 106 mm
Subwoofer	Bass reflex, powered	Surround	101 x 175 x 116 mm
Drivers		Subwoofer	230 x 425 x 412 mm
Front	8 cm cone	Weight	
Center	8 cm cone	Front	0.7 kg
Surround	8 cm cone	Center	1.0 kg
Subwoofer	20 cm cone	Surround	0.7 kg
Frequency Response		Subwoofer	9.1 kg
Front/Center	80 Hz–20 kHz	■ CARTON	
Surround	80 Hz–20 kHz	Dimensions (W x H x D)	
Subwoofer	27 Hz–150 Hz	541 x 466 x 505 mm	
Output Sound Pressure Level		Weight	
Front	81 dB/W/m	17.0 kg	
Center	82 dB/W/m		
Surround	81 dB/W/m		
Max. Input Power			
Front/Center/Surround	120 W		
Max. Output Power			
Subwoofer	150 W		
Nominal Impedance			
Front/Center/Surround	6 Ω		
Input Sensitivity/Impedance			
Subwoofer	140 mV/20 kΩ		

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice.