

Sub series



Our subwoofer models bring true Dynaudio performance to any home cinema or stereo music system. Sub 3 and Sub 6 are both designed to mesh seamlessly with any Dynaudio loudspeaker for fast, deep, precise and natural bass.

DYNAUDIO



Sub 3



Sub 6

Sub series

Data	Sub 3	Sub 6
System	Single driver, active subwoofer	Twin opposed driver, closed box, active DSP subwoofer
Analog inputs	1x RCA LFE, 2x RCA Stereo	2x balanced XLR, 2x unbalanced RCA phono
Analog outputs	1x RCA Slave Out, 2x RCA SAT Out	2x balanced XLR, 2x unbalanced RCA phono
Frequency response (\pm 3dB)	22Hz–175Hz	16Hz–230Hz
Auto ON/OFF	Yes	Yes
Box principle	Sealed	Sealed
High pass filter	Flat/60/80Hz	-
Low pass filter	50Hz–150Hz	Adjustable/preset
Phase adjustment	0/180 degrees	0/180 degrees
Woofer	24cm MSP	2x24cm MSP+ Hybrid Drive
Amplifier power	300W	500W
AC power input	100-240V 50/60Hz	100-240V 50/60Hz
Standby power consumption	<0.5W	<0.5W
Maximum power consumption	350W	490W
Weight	10.5kg/23.1lb	21.5kg/45.2lb
Dimensions (WxHxD)	266x276x320mm 10.5x10.9x12.6in	447x300x268mm 17.6x11.8x10.6in
Dimensions with feet/grille (WxHxD)	266x276x336mm 10.5x10.9x13.2in	470x333x268mm 18.5x13.1x10.6in

Finishes/grilles: Black Satin, White Satin



Sub
Designed and engineered
by Dynaudio Labs
in Denmark

Learn more, get the latest tips and tricks and read our reviews on
[dynaudio.com](https://www.dynaudio.com) and [facebook.com/dynaudiogroup](https://www.facebook.com/dynaudiogroup)

DYNAUDIO

Dynaudio A/S
Sverigesvej 15
8660 Skanderborg
Denmark

[dynaudio.com](https://www.dynaudio.com)

Product Series Insert, Sub
Item no. 45538210F

All text and image copyrights reserved
Subject to change without notice