

C-308ASWi



PREMIUM PERFORMANCE, PREMIUM FINISH

The all new C-Series subwoofers take performance and style to a new level. With a front-firing Cerametallic™ active woofer powered by a BASH digital hybrid amplifier, the C-308ASWi uses side-firing passive radiators to optimize output and low frequency extension while mimizing cabinet size. The hand polished piano gloss finish allows it to live as high end furniture in any listening environment.

MULTIPLE INPUTS FOR ANY SOURCE

The high powered BASH amplifier features separate RCA line, XLR balanced line, high level, and high definition wireless (with optional Klipsch WA-3 Wireless Transmitter) which are each independantly controlable in the Klipsch LowControl App - making a truly customized and fine-tuned listening experience for any source and any content.

KLIPSCH LOWCONTROL™ APP

The free Klipsch LowControl™ app for iOS and Android devices puts full control, customization, and tuning of the C-Series subwoofers right in the palm of your hand. With 5-band parametric EQ, phase, volume, input selection control, you can unleash the full power of your C-Series subwoofer from anywhere in the room.

AUTOMATIC ROOM CORRECTION

Tune the performance of your C-Series subwoofer to your room with the automatic room correction software included on the Klipsch LowControl™ app. Utilizing the microphone built into your device, the app provides fast and easy automatic room correction, compensating for any natural nulls or peaks in the room, for balanced, dynamic low frequencies in any environment.

IP CONTROL

A built-in RJ-45 connector allows for full integration into Control4, Crestron, Savant, and RTI control systems - meaning the subwoofer can automatically change input, EQ, gain, and phase settings when you simply select a new source or activity in your control system, to best match the source material being played.

WIRELESS COMPATIBILITY

With the optional WA-3 transmitter, the C-Series subwoofers can be placed anywhere in a room and receive high definition signal via 2.4GHz high definition wireless transmission. The receiver chip is built right into the amplifier circuitry, so there is no ugly dongle on the subwoofer - just the great sound you expect from a Klipsch subwoofer...completely wirelessly.

SPECIFICATIONS

FREQUENCY RESPONSE	28Hz - 150Hz +/- 3dB
MAXIMUM ACOUSTIC OUTPUT	110dB @ 35Hz, 1/8 Space, 1m
AMPLIFIER TYPE	BASH® Digital Hybrid
AMPLIFIER POWER	300W Continuous / 600W Peak
ACTIVE DRIVER	Front-Firing 8" (20.3 cm) Cerametallic™
PASSIVE RADIATORS	Dual Side-Firing 8" (20.3 cm) MDF
ENCLOSURE MATERIAL	MDF
ENCLOSURE TYPE	Bass Reflex via Dual Opposed Passive Radiators
INPUTS	Line-Level Dual RCA, Balanced Line-Level XLR, High-Level Speaker, 2.4GHz Wireless (With Optional WA-3 Transmitter)
HEIGHT	11-13/16" (29.9cm) with feet
WIDTH	11-4/16" (28.5 cm)
DEPTH	11-10/16" (29.5 cm) with grille
WEIGHT	27 lbs (12.2 kg)
FINISH	Hand Polished Piano Gloss Black
BUILT FROM	2018