Bronze Series 7G



The starting-point to high-fidelity.

Bronze Series 7G is a captivating class-leader. It is affordable as it is refined. Packed full of the latest acoustic technologies and created under the group Transparent Design Philosophy. All-new, Bronze is the starting point to high-fidelity.

















Bronze Series 7G

Enriched with the DNA of every Bronze Series that has gone before, expertly refined, developed and enhanced, Bronze Series 7G combines outstanding performance and contemporary design panache that will charm a new wave of followers and owners.

Available in stereo and AV options - the perfect speaker partner for Vestra Subwoofers - and maximising a level of quality and sonic excitement unheard of at this level. Bronze Series 7G really is the entry point to authentic high-fidelity sound.

- New C-CAM cone New C-CAM Gold Dome Tweeter New C-CAM bass and bass-mid drivers New crossover design Through-bolt driver bracing HiVe II ports











Model	Bronze 50 7G	Bronze 300 7G	Bronze Centre 7G	Bronze On-Wall 7G	Bronze AMS 7G Dolby Atmos [®] Enabled Speaker
System Format	2-Way	2.5-Way	2-Way	2-Way	2-Way
Frequency Response, In-Room (-6dB)	35 Hz - 30 kHz	27 Hz - 30 kHz	55 Hz - 30 kHz	33 Hz - 30 kHz	99 Hz - 30 kHz
Nominal Impedance	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
Minimum Impedance (20Hz to 20kHz)	>4 Ohms	>4 Ohms	>4 Ohms	>6 Ohms	>4 Ohms
Maximum Peak SPL (AES75, Z-weighted)	112 dB	118 dB	119 dB	112 dB	110 dB
Continuous Power Handling (CTA 426-B)	100 W	150 W	120 W	100 W	60 W
Recommended Amplifier Power (RMS, Music Signal)	50 - 200 W	75 - 300 W	60 - 240 W	50 - 200 W	30 - 120 W
Bass Alignment	Ported - HiVe II	Ported - HiVe II	Sealed	Ported	Sealed
Port Tuning Frequency	47 Hz	38 Hz	N/A	47 Hz	N/A
Crossover Frequency	LF/HF: 3.0 kHz	LF/MF: 470 Hz MF/HF: 2.6 kHz	LF/HF: 2.7 kHz	LF/HF: 3.0 kHz	LF/HF: 4.8 kHz
Drive Unit Complement	1 x 1" (25 mm) C-CAM Gold Dome Tweeter with UD waveguide 1 x 6" (152 mm) C-CAM Bass-mid driver	1x 1" (25 mm) C-CAM Gold Dome Tweeter with UD waveguide 1x 6" (152 mm) C-CAM Bass-mid driver 1x 6" (152 mm) C-CAM Bass driver	1 x 1" (25 mm) C-CAM Gold Dome Tweeter with UD waveguide 2 x 6" (152 mm) C-CAM Bass-mid driver	1 x 1" (25 mm) C-CAM Gold Dome Tweeter with UD waveguide 1 x 6" (152 mm) C-CAM Bass-mid driver	1 x 1" (25 mm) C-CAM Gold Dome Tweeter with UD waveguide 1 x 4" (102 mm) C-CAM Bass-mid driver
Bass Alignment	Ported	Ported	Sealed	Ported	Sealed
External Dimensions with all accessories fitted (H x W x D)	335 x 185 x 328 mm (13 ^{3/16} x 7 ^{5/16} x 12 ^{15/16} ")	1005 x 269 x 392 mm (39 ^{9/16} x 10 ^{5/8} x 15 ^{7/16} ")	205 x 500 x 228 mm (8 ^{1/16} x 19 ^{11/16} x 9 ")	465 x 300 x 135 mm (18 ^{5/16} x 111 ^{3/16} x 5 ^{5/16} ")	173 x 185 x 302 mm (6 ^{13/16} x 7 ^{5/16} x 11 ^{7/8} ")
Packed Dimensions (H x W x D)	453 x 754 x 297 mm (17 ^{13/16} x 29 ^{11/16} x 11 ^{11/16} ")	1098 x 427 x 320 mm (43 ^{1/4} x 16 ^{13/16} x 12 ^{5/8} ")	618 x 307 x 307 mm (24 ^{5/16} x 12 ^{1/16} x 12 ^{1/16} ")	573 x 402 x 240 mm (22 ^{9/16} x 15 ^{13/16} x 9 ^{7/16} ")	271 x 382 x 370 mm (10 ^{11/16} x 15 ^{1/16} x 14 ^{9/16} ")
Net Weight (Each)	6.4 kg (14 lb 2 oz)	15.6 kg (34 lb 6 oz)	7.9 kg (17 lb 7 oz)	7.0 kg (15 lb 7 oz)	3.1 kg (6 lb 13 oz)
Packaged Gross Weight (Pair)	15.2 kg (33 lb 8 oz)	N/A	N/A	N/A	7.3 kg (16 lb 1 oz)
Packaged Gross Weight (Single)	N/A	19 kg (41 lb 14 oz)	9.3 kg (20 lb 8 oz)	8.3 kg (18 lb 5 oz)	N/A
Finishes	Black / White / Walnut	Black / White / Walnut	Black / White / Walnut	Black / White / Walnut	Black / White / Walnut
Sold as	Pair	Pair	Single	Single	Pair
RRP (GBP, EUR, USD)	£500 / €600 / \$700	£1,000 / €1,250 / \$1,400	£400 / €500 / \$550	£300 / €350 / \$400	£450 / €575 / \$625
EAN	Black: 5061070620579 White: 5061070620586 Walnut: 5061070620593	Black: 5061070620548 White: 5061070620555 Walnut: 5061070620562	Black: 5061070620630 White: 5061070620647 Walnut: 5061070620654	Black: 5061070620661 White: 5061070620678 Walnut: 5061070620685	Black: 5061070620609 White: 5061070620616 Walnut: 5061070620623

■● Dolby Atmos