

Primare I15 MM Preliminary Specifications

I15 integrated amplifier, features 60 watts of power per channel, and an optional moving magnet phono preamplifier module, **MM15**, available for installation at any time. I15 utilises the same Hypex all analog class D power module as used in the EISA award winning I15 Prisma. But, without the need to provide power to the digital to analog conversion stage and network player found in the I15 Prisma, the power supply has been configured to allow I15 to perform with even greater drive and detail.

Output Power	2 x 60W 8 Ohm / 2 x 100W 4 Ohm
Frequency Response	20Hz-20KHz -0.7dB
THD + N	<0.02%, 20Hz-20KHz, 10W at 8 Ohm
Signal to Noise	>97dB
Crosstalk 10KHz	80dB
Input impedance	15K Ohm
Gain Speaker Out	42.5dB
Gain PRE Out	16.5dB
Gain Line Out	0dB

MM15 Phono Stage (optional)

Gain 1KHz	40.5dB
Gain Speaker Out	83dB
Resistance loading	47 K Ohm
Capacitive loading	150pF
RIAA Correction	+/- 0.2dB
Signal to Noise	78dB

Power Consumption

Standby	<0.5W
Operating	<20W

Dimensions

Width	350mm
Depth	339mm with knobs and connectors
Height	73mm
Weight	6.5Kg

Note: features and specifications are preliminary and subject to change.

