

# SKS-HT728

5.1-Channel Home Theatre Speaker System

BLACK



## Beautifully Balanced Surround-Sound System with Tallboy Front Speakers

For maximum audio impact, your multichannel Onkyo receiver should be accompanied by a full-blooded surround-sound speaker set. Fitting the bill is the new SKS-HT728, a 5.1-channel system that injects power and vitality into all your movies, games, and music. The highlight, both visually and aurally, is a pair of dual-drive, floor-standing tallboy front speakers rated conservatively at 130 W. In concert with the two-way center and full-range surround speakers—each also rated 130 W—they deliver stunningly detailed high- and mid-range frequencies. Meanwhile, at the bottom end, a superbly calibrated 290 W subwoofer adds visceral heft to bass notes and low frequency effects.

### SKF-770 Dual-Drive 2-Way Front Speakers

- 8 cm Cone Woofer x 2
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Gloss-Finished Top Panel

### SKC-770 Dual-Drive 2-Way Center Speaker

- 8 cm Cone Woofer x 2
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Gloss-Finished Side Panels

### SKR-770 Full-Range Surround Speakers

- 8 cm Cone
- Max. Input Power: 130 W

*Note: All speakers feature an impedance of 6  $\Omega$  and color-coded speaker terminals and cable. And all except the front speakers are wall-mountable.*

### SKW-770 Bass Reflex Powered Subwoofer

- 25 cm Cone
- Max. Output Power: 290 W
- Output-Level Control
- Gloss-Finished Front Panel

## SPECIFICATIONS

Speaker Type	
Front	Dual-drive, 2-way
Center	Dual-drive, 2-way
Surround	Full-range
Subwoofer	Bass reflex, powered
Drivers	
Front	8 cm cone woofer x 2 2.5 cm balanced-dome tweeter
Center	8 cm cone woofer x 2 2.5 cm balanced-dome tweeter
Surround	8 cm cone
Subwoofer	25 cm cone
Frequency Response	
Front	55 Hz–50 kHz
Center	60 Hz–50 kHz
Surround	80 Hz–20 kHz
Subwoofer	25 Hz–150 Hz
Output Sound Pressure Level	
Front	79.5 dB/W/m
Center	79 dB/W/m
Surround	81 dB/W/m
Max. Input Power	
Front/Center/Surround	130 W
Max. Output Power	
Subwoofer	290 W

Nominal Impedance	
Front/Center/Surround	6 $\Omega$
Input Sensitivity/Impedance	
Subwoofer	140 mV/20 k $\Omega$
GENERAL	
Dimensions (W x H x D)	
Front (not including speaker base)	
	262 x 1050 x 262 mm
Center	430 x 115 x 121 mm
Surround	115 x 230 x 96 mm
Subwoofer	275 x 507 x 411 mm
Weight	
Front	5.2 kg
Center	2.2 kg
Surround	1.0 kg
Subwoofer	11.6 kg
■ CARTON	
Dimensions (W x H x D)	
	683 x 1150 x 558 mm
Weight	
	35 kg

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice.

**ONKYO**  
 IMAGINATIVE SIGHT & SOUND

Onkyo Corporation 2-1 Nisshin-cho, Neyagawa-shi, Osaka 572-8540, JAPAN Tel: +81-72-831-8136 Fax: +81-72-833-5222 <http://www.onkyo.com/>  
 Onkyo China Limited Unit 1 & 12, 9/F, Ever Gain Plaza Tower 1, 88 Container Port Road, Kwai Chung, N.T., Hong Kong, SAR of CHINA Tel: +852-2429-3118 Fax: +852-2428-9039 <http://www.ch.onkyo.com/>  
 Onkyo U.S.A. Corporation 18 Park Way, Upper Saddle River, N.J. 07458, U.S.A. Tel: +1-201-785-2600 Fax: +1-201-785-2650 <http://www.onkyousa.com/>  
 Onkyo Europe Electronics GmbH Liegnitzerstrasse 6, 82194 Grobenzell, GERMANY Tel: +49-8142-4401-0 Fax: +49-8142-4401-555 <http://www.eu.onkyo.com/>