

# SKS-HT648 5.1-CHANNEL HOME CINEMA SPEAKER SYSTEM



## Round Out Your Home Cinema with Compact Surround Sound

Introducing an affordable speaker set that will bring a deeper dimension to your movies, games, and music. Comprising a powered subwoofer, two-way front and center speakers, and full-range satellites—all gloss-finished—the SKS-HT648 delivers lifelike surround sound with finesse. Here, style is backed by serious substance. Subtle front-on curves are complemented by a rounded rear section that counteracts unwanted standing waves. Cradle one of these speakers in your palm and you'll feel a reassuring heft. Reason? It's Onkyo's newly developed high-density resin, which provides superb rigidity and resistance to vibration. The down-firing subwoofer, meanwhile, employs a 20 cm cone to deliver a tight and balanced low-end.

### SKF-648

2-Way Acoustic Suspension  
Front Speakers

- 8 cm Cone Woofer
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Gloss Finished
- Magnetically Shielded

### SKC-648

2-Way Acoustic Suspension  
Center Speaker

- 8 cm Cone Woofer x 2
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Gloss Finished
- Magnetically Shielded

### SKR-648

Full-Range Acoustic Suspension  
Surround Speakers

- 8 cm Cone
- Max. Input Power: 130 W
- Gloss Finished
- Magnetically Shielded

*Note: All speakers feature an impedance of 6  $\Omega$  and color-coded speaker terminals and cable.*

### SKW-501E

Bass Reflex Powered Subwoofer

- 20 cm Cone
- Rated Output Power: 80 W (Minimum Continuous Power; 4  $\Omega$ , 100 Hz, 1%, IEC)
- Down-Firing
- Gloss Finished
- Output Level Control

## SPECIFICATIONS

<b>Speaker Type</b>		<b>Rated Output Power</b>	
Front	2-way, Acoustic suspension	Subwoofer	80 W (Minimum continuous power; 4 $\Omega$ , 100 Hz, 1%, IEC)
Center	2-way, Acoustic suspension	<b>Nominal Impedance</b>	
Surround	Full-range, Acoustic suspension	Front/Center/Surround	6 $\Omega$
Subwoofer	Bass reflex, Powered	<b>Input Sensitivity/Impedance</b>	
<b>Drivers</b>		Subwoofer	410 mV/20 k $\Omega$
Front	8 cm cone woofer	<b>General</b>	
Center	2.5 cm balanced-dome tweeter	<b>Dimensions (W x H x D)</b>	
Surround	8 cm cone woofer x 2	Front	102 x 170 x 105 mm
Subwoofer	2.5 cm balanced-dome tweeter	Center	277 x 110 x 110 mm
<b>Frequency Response</b>		Surround	102 x 170 x 105 mm
Front	70 Hz–50 kHz	Subwoofer	230 x 425 x 412 mm
Center	70 Hz–50 kHz	<b>Weight</b>	
Surround	80 Hz–20 kHz	Front	1.0 kg
Subwoofer	27 Hz–150 Hz	Center	1.7 kg
<b>Output Sound Pressure Level</b>		Surround	0.9 kg
Front	79 dB/W/m	Subwoofer	9.1 kg
Center	82 dB/W/m	<b>CARTON</b>	
Surround	80 dB/W/m	<b>Dimensions (W x H x D)</b>	
<b>Max. Input Power</b>		Front/Center/Surround	566 x 480 x 464 mm
Front/Center/Surround	130 W	<b>Weight</b>	
		18.0 kg	

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice.