

A-30-S

Direct Energy Design Integrated Amplifier with Symmetrical Construction, Aluminium Rotary Knob and Panels, and Phono MM



REAR PANEL



A-30-S/PWSYXE8

DESIGN & BUILD

- > Direct Energy Design Amp
- > Symmetrical Power Amp
- > Clean Ground Construction
- > Isolated Power Supply
- > Source Direct Mode
- > Power Amp Direct Mode
- > Trans-Stabilizer
- > Speaker A, B, A+B Selector
- > Aluminium Rotary Knob
- > Aluminium Panels
- > Auto Power Down

CONNECTIONS

- > Analogue Audio Input (PHONO (MM), TUNER, SACD/CD, AUX, NETWORK, RECORDER, POWER AMP DIRECT IN)
- > Audio Output (RECORDER, PHONES)
- > SR In/Out
- > AC Inlet

SPECIFICATIONS

- > 70 W + 70 W (20 Hz-20 kHz, THD 0.1 %, 4 ohms)
- > 40 W + 40 W (20 Hz-20 kHz, THD 0.05 %, 8 ohms)
- > THD: 0.01 % (Rated Output -3 dB, 8 ohms, 1 kHz)
- > Guaranteed Speaker Impedance (2 Speaker Terminals): 4-16 ohms (A or B), 8-32 ohms (A+B), 4-16 ohms (Bi-Wiring)
- > Frequency Response: SACD/CD 5 Hz-100 kHz, 0 dB/-3 dB, PHONO (RIAA Equalization) MM 20 Hz-20 kHz, ± 0.5 dB
- > Signal-to-Noise Ratio (IHF, A Network, Short Circuited) SACD/CD: 105 dB, Phono: 77 dB (MM: 5 mV input), Power Amp Direct: 118 dB
- > Channel Separation SACD/CD: 90 dB (100 Hz), 90 dB (1 kHz), 75 dB (10 kHz) Power Amp Direct: 90 dB (100 Hz), 90 dB (1 kHz), 85 dB (10 kHz)
- > Power Requirements: AC 220-230 V, 50 Hz
- > Power Consumption: 175 W
- > Power Consumption During Standby: 0.3 W
- > Dimensions (W x H x D): 435 x 128 x 360 mm
- > Weight: 7.9 kg

INTEGRATED TECHNOLOGIES



This logo is used for Pioneer products capable of 96 kHz/24-bit or above WAV/FLAC file playback, and Pioneer amplifiers, speakers, or headphones supporting over 40 kHz high-frequency reproduction, designed to derive maximum performance from Hi-Resolution Audio. This logo is a registered trademark of Japan Audio Society.