

DacMagic 100 Digital to Analogue Converter

Feb 2012



- Digital to Analogue Converter featuring S/PDIF and Toslink digital inputs and USB audio input (all 24 bit compatible)
- Wolfson WM8742 24bit DAC
- 24-bit/96kHz driverless USB Audio 1.0 input
- 24-bit/192kHz USB Audio 2.0 input with ASIO or kernel streaming modes
- Asynchronous USB transfer for very low jitter USB Audio input allowing streaming of up to 24-bit/192kHz audio from computer
- USB audio input allows the DacMagic 100 to act as a high quality DAC/soundcard for your computer
- RCA audio output
- Full metal casework design with thick brushed aluminium front panel
- Available in black or silver finishes

Detailed Specifications

Digital inputs	2 x S/PDIF 75 ohms 1 x TOSLink optical
USB Audio Input	USB Type B conforming to Audio profile 1.0 or USB Audio profile 2.0 (user 1.0 or USB Audio profile 2.0 (user selectable)
Audio Output	1 x pair Gold Plated RCA phono outputs
D/A converter	Wolfson WM8742 24bit DAC
Frequency response	20Hz to 20kHz (± 0.1 dB)
Digital input word widths supported	16-24bit
Digital input sampling frequencies supported on all inputs	32kHz, 44.1kHz, 48kHz, 88.2kHz, 96kHz, 192kHz *
Output level (unbalanced)	2.3V rms
Output impedance	<50ohms
Max power consumption	5W
Dimensions (H x W x D)	46 x 106 x 130mm
Weight	0.5kg/1.1lbs

* Toslink input supports 96kHz maximum



DacMagic 100 Digital to Analogue Converter