



D 8020 Compact Monitor



SPECIFICATIONS		
Frequency Response	On Axis @ 0° ± 3dB On Axis @ 0° ± 1 1/2dB Off Axis @ 30° ± 3dB LF Cutoff -10dB	80-22,000Hz 90-20,000Hz 90-12,000Hz 58Hz
Sensitivity (1W (2.83V) @ 1m, IEC-filtered Pink Noise, C-weighted)		84dB
Impedance	Nominal Minimum	8 Ohms 6 Ohms
Input Power	Recommended Program	15-80 Watts 60 Watts
Acoustic Design	Tweeter (Nominal) Woofer (Nominal)	3/4" (19mm) Black Anodized Aluminium Dome 3 1/2" (90mm) Polypropylene Cone, Rubber Surround
Crossover		2100Hz, LR4
Internal Volume		0.067 ft ³ (1.9 litres)
Design Type		Bass Reflex Rear Slot Port
GENERAL		
Unit Dimension (WxHxD) - Gross* (includes grille, knobs, terminals and mounting brackets)		4 1/2 x 7 7/8 x 6 7/8" 114 x 197 x 174mm
Net weight		3.8lb (1.72kg)
Shipping weight		36.2lb (16.5kg)
Finish		Gloss Black
Features		5-way Gold-plated Binding Posts
Optional Accessories		15° Tilted Base (pair)

* Non-metric measurements are approximate.

NAD Electronics International reserves the right to change specifications or features without notice. NAD is a registered trademark of NAD Electronics International. All rights reserved. No part of this publication may be reproduced, stored, or transmitted in any form whatsoever without the written permission of NAD Electronics International. © 09/14 14-042 NAD Electronics International.

www.NADelectronics.com